

1 47634/GTL/F161

What is Claimed is:

5 1. A seal device prepared by the process of shape forming  
a composite construction into a desired seal device shape, the  
composite construction comprising a polymer material disposed  
onto a rigid nonpolymeric substrate prior to the step of shape  
forming, the seal device comprising a seal body having a casing  
10 member formed from the rigid substrate, and a compliant sealing  
element formed from the polymer material.

15 2. The seal device as recited in claim 1 wherein the  
polymer material is configured having a high surface area  
comprising a plurality of ridges and valleys.

20 3. The seal device as recited in claim 1 wherein the  
sealing element projects outwardly beyond a length of the casing  
member and includes a sealing lip for providing a seal against  
a sealing surface.

25 4. The seal device as recited in claim 1 wherein the seal  
device is formed from two composite constructions that are joined  
together and that each comprise a rigid substrate and a  
respective polymer material.

5. The seal device as recited in claim 4 wherein each  
polymer material forms a separate compliant sealing element.

30 6. The seal device as recited in claim 1 wherein the  
sealing element comprises a sealing surface having a contact  
surface configured to resist fluid leakage.

35 7. The seal device as recited in claim 1 wherein the  
casing member includes a deformed portion adjacent an inside

1 47634/GTL/F161

diameter casing end that imposes a desired urging force onto the compliant sealing element.

5

8. The seal device as recited in claim 1 wherein the casing member has an L-shaped cross-sectional configuration.

9. The seal ring as recited in claim 1 wherein the casing member has a U-shaped cross-sectional configuration.

10. A seal device prepared by the process of:  
depositing a polymer material onto a rigid nonpolymeric substrate to form a composite construction; and  
15 shape forming the composite construction into a desired shape;  
wherein the sealing device comprises a seal body having:

a casing member that is formed from the rigid substrate;  
and  
a sealing element formed from the polymer material and  
20 disposed along a surface of the casing member for placement against a dynamic sealing surface.

11. The seal device as recited in claim 10 wherein the casing member is in the form of a metallic ring and defines an  
25 outside diameter of the seal device, wherein the sealing element is positioned radially inwardly of the casing member, and wherein the sealing element includes a contact surface that projects outwardly and away from the casing member for placement against the dynamic sealing surface.

30

12. The seal device as recited in claim 10 wherein the casing member is in the form of a metallic ring and defines an inside diameter of the seal device, wherein the sealing element is positioned radially outwardly of the casing member, and  
35 wherein the sealing element includes a contact surface that

projects outwardly and away from the casing member for placement against the dynamic sealing surface.

5

13. The seal device as recited in claim 10 wherein the polymer material has a high surface area provided by a plurality of topographical surface features.

10 14. The seal device as recited in claim 10 wherein the casing member is configured to provide a determined degree of resiliency to the sealing element.

15 15. The seal device as recited in claim 10 wherein the seal device is formed from two composite constructions that are joined together and that each comprise a rigid substrate and a respective polymer material.

20 16. The seal device as recited in claim 15 wherein the two composite constructions are joined together between rigid substrates.

25 17. The seal device as recited in claim 15 wherein the two composite constructions are joined together by mechanical interlocking, and wherein the rigid substrates are separated from one another by one of the polymer materials.

30 18. The seal device as recited in claim 15 comprising dual sealing elements formed from respective composite construction polymer materials, wherein each sealing element projects outwardly a distance away from a respective rigid substrate, and includes a sealing surface for making contact with an adjacent dynamic sealing surface when placed into service.

35

1 47634/GTL/F161

19. The seal device as recited in claim 18 wherein the  
sealing elements each project outwardly away from a respective  
5 rigid substrate in the same general direction.

20. The seal device as recited in claim 10 wherein the  
casing member includes a deformed portion adjacent an inside  
diameter casing end that imposes a desired urging force onto the  
10 sealing element.

21. A method for making a seal device from a preformed  
polymer laminated metallic construction, the method comprising  
the steps of:

15 placing a polymer material layer onto a metallic substrate  
and chemically bonding the polymer material layer thereto to form  
a polymer laminated metallic constriction;

shape forming the polymer laminated metallic construction  
into a desired shape; and

20 trimming the shaped formed construction into a desired seal  
device configuration;

wherein the sealing device comprises:

a casing member that is formed from the metallic substrate;  
and

25 a sealing element that is formed from the polymer material,  
and that includes a contact surface that projects outwardly and  
away from the casing member for sealing placement against an  
adjacent dynamic sealing surface when placed into service.

30 22. The method as recited in claim 21 wherein the polymer  
laminated metallic constriction is in sheet form prior to shape  
forming.

35

1 47634/GTL/F16i

23. The method as recited in claim 21 wherein the polymer material is configured having a high surface area made up of a plurality of topographical features prior to shape forming.

24. The method as recited in claim 21 wherein the casing member is in the form of a ring having an L-shaped configuration, and the sealing element contact surface extends radially inwardly away from the casing member.

25. The method as recited in claim 21 wherein the sealing device is formed from two polymer laminated metallic constructions, and further comprises the step of joining together the two shaped formed casing members and respective sealing elements.

26. The method as recited in claim 25 wherein the step of joining comprises bonding together the two casing members.

27. The method as recited in claim 25 wherein the step of joining comprises deforming a portion of at least one of the casing members towards an adjacently position portion of the other one of the casing members.

28. The method as recited in claim 25 wherein during the joining step the two polymer laminated metallic constructions are combined so that the two case members are placed into contact with one another.

29. The method as recited in claim 25 wherein during the joining step the two polymer laminated metallic constructions are combined so that the two sealing elements are placed into contact with one another.

1 47634/GTL/F161

30. The method as recited in claim 25 wherein during the  
joining step the two polymer laminated metallic constructions are  
5 combined so that the two case members are separated from one  
another by one of the sealing elements.

31. The method as recited in claim 21 wherein during the  
shape forming step the casing member is deformed along a portion  
10 adjacent an inside diameter casing member end to impose a desired  
urging force onto the sealing element.

15

20

25

30

35